

EBOX-336x Series, LAN x 1, RS-232, SATA

Model Type	EB-3360-S3	EB-3360-C1	EB-3360-C2	EB-3360-C3	EB-3360-C4
Processor	EB-3362-S3	EB-3362-C1	EB-3362-C2	EB-3362-C3	EB-3362-C4
BIOS	DM&P Vortex86DX3 (1GHZ)				
Memory	Onboard 1GB DDR3 for 3360 Series/ Onboard 2GB DDR3 for 3362 Series				
VGA	Integrated Graphics Chip/ D-Sub 15-pin 1920 x 1080 pixels				
Maximum Resolution	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)				
Ethernet	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port				
USB 2.0	Line out				
H/D Audio	1x				
SD Slot	1x				
SATA	1x				
COM1	RS-232	RS-232	RS-232	RS-232	RS-232
COM2	N/A	RS-232	RS-232	RS-232	RS-232
COM3	N/A	N/A	RS-232	RS-232	RS-232
COM4	N/A	N/A	N/A	N/A	RS-232
Auto Power On	Yes				
Power	DC +8V~+24V				
Dimensions	115 x 115 x 35mm				
Unit Net Weight	510g				
Operation Temp.	5~50°C				
Certifications	CE, FCC, VCCI				
Optional	1. Mic input 2. Internal SD Card slot 3. TTL Level RS-232 4. mPCIe (2.5" SATA HDD not support)				
Note	RS-232 COM ports in Full 9pin				

Features:

- DM&P Vortex86DX3 (1GHZ)
- Onboard 1GB/ 2GB DDR3
- SATA DOM, 2.5" HDD, SSD support
- mSATA support (mSATA to SATA adapter required)
- SD, SDHC support
- VESA mounting support
- Fanless design
- 10/100 Mbps LAN x 1
- WiFi Dongle support (Optional)
- PXE Diskless Boot
- USB 2.0 port x 4
- RS-232 Up to 4 ports (Optional)
- Auto Power On support
- Ultra low power

