

DIN PC-333x Series

Model Type	D-3330-SS D-3332-SS	D-3330-C1851 D-3332-C1851	D-3330-C2 D-3332-C2	D-3330-C4 D-3332-C4	D-3330-851221 D-3332-851221	D-3330-851221C2 D-3332-851221C2
Processor	DM&P Vortex68DX2 (933MHz)					
BIOS	AMI BIOS					
Memory	Onboard 1GB DDR2 for 3330 Series/ Onboard 2GB DDR2 for 3332 Series					
VGA	Integrated Graphics Chip/ D-Sub 15-pin 1920 x 1440 pixels					
Maximum Resolution	10/100 Mbps LAN x 1, 1G LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)					
Ethernet	Ethernet: 2 ports (Front x 2) Internal: 1 port (space reserved dimension 33 x 20mm)					
USB 2.0	1x (Internal)					
SD Slot	1x (Internal)					
SATA	1x					
COM1	RS-232	RS-232	RS-232	RS-485	RS-485	RS-485
COM2	RS-485	RS-232	RS-232	RS-422	RS-422	RS-422
COM5	N/A	N/A	RS-232	N/A	RS-232	RS-232
COM6	N/A	N/A	RS-232	N/A	RS-232	RS-232
Auto Power On	Yes					
Power	DC +8V~+24V (Pluggable Terminal Block 3-Pin 5.00mm Pitch)					
Dimensions	152 x 104 x 54mm					
Unit Net Weight	760g					
Operation Temp.	5~50°C					
Certifications	CE, FCC, VCCI					
Optional	1. Mic Input/ Line out 2. TTL Level RS-232					
Note	RS-232 COM ports in Full 9pin					

Model Type	D-3330-892 D-3332-892	D-3330-892C2 D-3332-892C2	D-3330-221C1 D-3332-221C1	D-3330-222 D-3332-222	D-3330-222C2 D-3332-222C2
Processor	DM&P Vortex68DX2 (933MHz)				
BIOS	AMI BIOS				
Memory	Onboard 1GB DDR2 for 3330 Series/ Onboard 2GB DDR2 for 3332 Series				
VGA	Integrated Graphics Chip/ D-Sub 15-pin 1920 x 1440 pixels				
Maximum Resolution	10/100 Mbps LAN x 1, 1G LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)				
Ethernet	Ethernet: 2 ports (Front x 2) Internal: 1 port (space reserved dimension 33 x 20mm)				
USB 2.0	1x (Internal)				
SD Slot	1x (Internal)				
SATA	1x				
COM1	RS-485	RS-485	RS-422	RS-422	RS-422
COM2	RS-485	RS-485	RS-232	RS-422	RS-422
COM5	N/A	RS-232	N/A	RS-232	RS-232
COM6	N/A	RS-232	N/A	RS-232	RS-232
Auto Power On	Yes				
Power	DC +8V~+24V (Pluggable Terminal Block 3-Pin 5.00mm Pitch)				
Dimensions	152 x 104 x 54mm				
Unit Net Weight	760g				
Operation Temp.	5~50°C				
Certifications	CE, FCC, VCCI				
Optional	1. Mic Input/ Line out 2. TTL Level RS-232				
Note	RS-232 COM ports in Full 9pin				

35

Features:

- DM&P Vortex68DX2 (933MHz)
- Onboard 1GB 2GB DDR2
- SATA DOM support
- SATA 2.5" HDD, SSD support (Optional)
- mSATA support (mSATA to SATA adapter required)
- SD, SDHC support (Internal)
- DIN rail mounting support
- Fanless design
- 10/100 Mbps LAN x 1, 1Gbps LAN x 1
- WIFI Dongle support (Optional)
- PXE Diskless Boot
- USB 2.0 port x 3
- RS-232 Up to 4 ports (Optional)
- RS-485 Up to 2 ports (Optional)
- RS-422 Up to 2 ports (Optional)
- Auto Power On support
- Pluggable Terminal Block 3-Pin 5.00mm Pitch

36

