

C800

Ultra-light x86 Thin Client supporting Microsoft RDP, Citrix, VMware View



Feature

- Ultra-light and fanless design
- Designed with Intel Bay Trail-M platform dual core CPU
- Support Microsoft RDP, Citrix, VMware View
- Optional WLAN module
- Support Kensington lock and VESA mount



Specification		Model no.	C800
Processor	CPU		Intel Bay Trail M - Celeron N2807 Dual Core 1.58 GHz SoC
Memory	RAM		1 x SO-DIMM socket for DDR3L-1333 RAM
Display	Resolution		Up to 1920 x 1200
Audio	Speaker		x 1 (Build-in 1W internal speaker)
Storage			a. Onboard eMMC (starting from 4GB) b. mSATA Conn. x 1
I/O Physical	USB (1.1/2.0)	Front	x 3
	USB (3.0)	Rear	x 1
	Video	DVI	x 2 (DVI-I, DVI-D)
	Audio	Mic-in	x 1
		Line-out	x 1
Networking	LAN		x 1 (RJ-45, 10/100/1000 Base T)
	WLAN		x 1 (Optional)
Environment	Temperature	Operation	32° to 95° F (0° to 35° C)
		Storage	-4° to 140° F (-20° to 60° C)
	Relative Humidity		20% to 80% non-condensing
Power	Power Supply		24W, DC 12V /2A external wall mount type power adapter
Mounting	Foot Stand	H or V	Vertical
	VESA Bracket		Metal mounting kit for VESA standard (optional)
Security	Kensington Lock		Yes
OS Support			Win7(WES7, WinCE7), Win8/8.1(WES8), Linux
Physical Characteristics	Chassis Housing		Plastic and metal
	Dimension / Weight	Terminal	29(W) x 155(H) x 133(D) mm / NW : 0.6 KG
		Packing: Single Box	83 (W) x 232 (H) x 205 (D) mm / GW: 1.1 KG
		Packing: Carton	662 (W) x 265 (H) x 355 (D) mm / GW: 13.2 KG, 12 boxes in one carton
Regulatory Compliance			CE / FCC

Specifications subject to change without notice.

Mechanical Layout/ Drawing

Front Side View

Rear Side View



Front Side View

1. Power button
2. USB 2.0 ports x 3
3. Audio port (Line-out)
4. Audio port (MIC-in)
5. Cradle

Rear Side View

6. External antenna port
7. USB 3.0 port
8. RJ-45 LAN port
9. Audio port (MIC-in)
10. DVI-I port
11. DC jack
12. Kensington Lock