

epatec

Item	Description
Model	PANEL PC 15YL I5
CPU	Intel Haswell Core i5 4200U dual core 1.6G , 3M Third Cache
Chipset	Intel express chipset
RAM	1*SODIMM DDR3L (MAX 8G)
Display	Integrated Intel HD Graphic card ,support VGA、HDMI , LVDS
Port	display input
Touch LCD	15.0" TFT LCD, resolution: 1024 x 768, Brightness (cd/m2):350, LCD power consumption :7.5 W , Contrast ratio (1000 : 1) , Viewing angle : 176(H)/176(V), Wide operating temperature
Expansion	1*Mini-PCIE, support wifi/3G
Port	
Storage	1*MINISATA, 1*7+15 Pin SATA
Audio	Integrated Realtek ALC662 6 sound channel
LAN	1*Intel RTL8111F 1000M Lan, support wake on lan (2*LAN is optional)
External I/O	2* COM(COM2 support RS422/485) 1* 12 DC IN 2* USB2.0 , 2*USB3.0 (Can up to 6*USB2.0, 2*USB3.0) 1* RJ-45 LAN 1* Mic, 1*Audio 1* VGA 1* HDMI

Internal I/O	2* group USB Pin Header 1* LVDS and LVDS INVERTER 1* CPUFAN and SYSFAN 1* JVGA Pin Header 1* JHDMI Pin Header 1* PS/2 Pin Heade 1* LPT Pin Header 1* 10 Pin GPIO Pin Header 1* 7 + 15 Pin SATA 1* SIM Slot
BIOS	64MB SMT Flash ROM
WDT	Support hardware level (256 level , 0~255 sec)
Power Supply	DC 12 V
Working Temp	-10°C ~ 60°C
Storage Temp	-20°C ~ 70°C
Humidity	5 ~ 90% relative humidity , non-condensing
Dimension	365 x 290 x 55 mm

epatec

